

# TYPE APPROVAL CERTIFICATE

**This is to certify:****That the Pressure Transmitter**with type designation(s)  
**PTM.MT/N/Ex**

Issued to

**STS Sensor Technik Sirnach AG**  
**Sirnach, TG, Switzerland**

is found to comply with

**DNV GL rules for classification – Ships, offshore units, and high speed and light craft****Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**

<b>Temperature</b>	<b>D</b>
<b>Humidity</b>	<b>B</b>
<b>Vibration</b>	<b>B</b>
<b>EMC</b>	<b>B</b>
<b>Enclosure</b>	<b>D</b>

Issued at **Hamburg** on **2021-02-10**for **DNV GL**This Certificate is valid until **2025-09-23**.DNV GL local station: **Augsburg**Approval Engineer: **Jens Dietrich**

---

**Joannis Papanuskas**  
**Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Job Id: **262.1-033928-2**  
Certificate No: **TAA00002VW**  
Revision No: **1**

## Product description

Submersible Level Transmitter for Maritime Applications:

Housing: Titanium, Sealing: Viton

Pressure measuring ranges: 0...400mbar, 0...1000mbar, 0...2500mbar, 0...4000mbar, 0...6000mbar.

Temperature range: -20...+100°C

Resolution: 0.025% FS

Adjustable output: 4...20mA

Modbus communication for scaling and calibration

Power supply 12...30VDC

PT100 (optional)

Fixed cable connection (FEP cable)

Degree of protection: IP68 (60m, 24h)

Ex-Certificates (for reference only): SEV 20 ATEX 0418 X, IECEx SEV 20.0018 X.

## Approval conditions

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV GL, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV GL rules for classification of ships Pt.4 Ch.9 Control and monitoring systems.

### Product certificate

If specified in the Rules, ref. Pt.4 Ch.9 Sec.1, the control and monitoring system in which the above listed hardware is used shall be delivered with a product certificate. For each such delivery the certification test is to be performed at the manufacturer of the application system before the system is shipped to the yard. The test shall be done according to an approved test program. After certification the clause for software control will be put into force.

For the use of the optionally integrated PT100 sensor self-heating is to be considered. Measurements cannot be taken of the analogue output during communication.

## Type Approval documentation

Data sheet 10.80.0577.B, 2020.11; User Manual 10.00.0579.A, dated 2020-09-25;

Drawings: 6.10.1466, rev.A, dated 2020-09-22; 9.99.0161.B, dated 2021-01-21.

Test reports: STS PRO-19-0020 Energieversorgungsausfall, V2.0, 2020-09-21; STS PRO-19-0020 Energieversorgungsschwankungen, V1.0, 2020-09-17; STS PRO-19-0020 Dichtigkeitsmessung V1.0, 2020-04-12; TEA AG, report UB14860, rev.0, issued 2020-07-07; Eurofins E&E, report 20CH-00795.E01, issued 2020-07-15. Data sheet for used cable: Pilotex Ref: 2PL746, Issue 6, 2018-11-22.

TA Assessment Report issued by DNV GL Augsburg, dated 2020-06-23.

Additional documents changed cable and glue: Data sheet BeWo Kabel Datenblatt 705080.J0119005, vers.1, dated 2020-10-28; Dichtigkeitsmessung Kabelabgang PTM.MT mit BEWO-Kabel, PRO-19-0020 V1.0, dated 2020-04-12; Dichtigkeitsmessung Kabelabgang PTM.MT mit BEWO-Kabel ohne Verguss, PRO-19-0020 V1.0, dated 2021-02-08; Data sheet 4.01.9026, rev.A, dated 2021-01-06; Data sheet 6.10.1405, rev.G, dated 2021-01-18; Statement Kleberwechsel Cyanolit zu Araldit, PRO-19-0020, ver. 1.0, dated 2021.

## Tests carried out

Applicable tests according to DNVGL CG-0339, December 2019.

## Marking of product

Maker, type designation, ratings, serial number.

## Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

Job Id: **262.1-033928-2**  
Certificate No: **TAA00002VW**  
Revision No: **1**

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE